dependent claims are in condition for allowance. The remaining prior art cited by the Examiner but not relied upon has been reviewed and is not believed to show or suggest the claimed invention.

No fee or extension of time is believed to be necessary; however, in the event that any fee or extension of time is required for the prosecution of this application, please charge it against Deposit Account No. **50-0563**.

Respectfully submitted,

Antony P. Ng
Registration No. 43,427
BRACEWELL & PATTERSON, LLP
111 Congress Ave., Suite 2300
Austin, Texas 78701
(512) 343-6116

ATTORNEY FOR APPLICANTS

REMARKS

Claims 9-16 and 21-40 have been cancelled. Thus, Claims 1-8 and 17-20 are currently pending in the present application, all of which have been amended.

Pursuant to the request from the Examiner, a substitute specification having double-line spacing while without any addition of new matters is enclosed herein.

Rejection under 35 U.S.C. § 102

Claims 1-40 were rejected under 35 U.S.C. § 102(e) as being anticipated by *Rakavy et al.* (US 6,324,644). Applicants respectfully traverse such rejection insofar as it might be applied to the claims as amended herein.

Amended Claim 1 (and similarly Claims 5 and 17) now recites a step of "storing a hardware setup program and a plurality of dynamic link modules in a server data processing system" (lines 3-4). Such hardware setup program and dynamic link modules are not found in the data processing systems disclosed in *Rakavy*.

Further, Claim 1 also recites a step of "de-coupling said data processing system from said server data processing system after a completion of said hardware setup operation" (lines 13-14). Since the purpose of present invention is to perform a hardware setup operation on a data processing system by coupling the data processing system to a server data processing system via a network, thus, the data processing system has to be de-coupled from the server data processing system after the hardware setup operation has been completed. Such de-coupling step is not taught or suggested in *Rakavy* because *Rakavy* is not related to performing hardware setup operation on a computer via a server. Since the claimed invention recites novel features that are not taught or suggested by *Rakavy*, the § 102 rejection is believed to be overcome.

CONCLUSION

Claims 1-8 and 17-20 are currently pending in the present application. For the reasons stated above, Applicants believe that independent Claims 1, 5 and 17 along with their respective

REDACTED CLAIMS

1.   (Amended) A <u>method for performing a</u> hardware setup <u>operation on a data processing</u> <u>system, said</u> method comprising:

storing a hardware setup program and a plurality of dynamic link modules in a server data processing system;

[accessing] <u>coupling a data processing system to</u> <u>said</u> server data processing system[, by a client data processing system,] via a data processing system network;

<u>in response to a request to execute said hardware setup program by said data</u> <u>processing system,</u> [requesting over the data processing system network] <u>executing said</u> [an execution of a] hardware setup program [by the] <u>within said</u> server data processing system;   .

[receiving, in the client data processing system, one or more dynamic link modules for a hardware setup operation; and]

modifying [the] hardware configuration data [on the client] <u>within said</u> data processing system according to instructions generated [by the] <u>from said execution of said</u> hardware setup program [on the] <u>within said</u> server data processing system<u>; and</u>

<u>de-coupling said data processing system from said server data processing system</u> <u>after a completion of said hardware setup operation.</u>

2.   (Amended) The [hardware setup] method of Claim 1, wherein[: if the] <u>when said</u> hardware setup operation required by [the client] <u>said</u> data processing system exists [on] <u>within</u> an operating system running on [the client] <u>said</u> data processing system, [the] <u>said</u> hardware setup program performs [the] <u>said</u> hardware setup operation by using a service provided by [the] <u>said</u> operating system.

3.   (Amended) The [hardware setup] method of Claim 1, wherein[:
the hardware setup operation is performed by changing one or more items of hardware configuration data on the client data processing system] <u>when said hardware setup operation</u> <u>required by said data processing system does not exist within an operating system running on said</u> <u>data processing system, said hardware setup program calls a BIOS program within said data</u> <u>processing system to perform said hardware setup operation.</u>

4.   (Amended) The [hardware setup] method of Claim 1, wherein <u>said method further</u> <u>includes transferring one or more of said dynamic link modules from said server data processing</u> <u>system to said data processing system via said data processing system network as a result of said</u> <u>execution of said hardware setup program</u> [:

if the hardware setup operation required by the client data processing system does not exist on an operating system running on a client data processing system, the hardware setup program calls a BIOS program on the client data processing system, and uses the BIOS program to perform the hardware setup operation].

5.   An apparatus for performing a hardware setup operation on a data processing system, said apparatus [method] comprising:

   means for storing a hardware setup program and a plurality of dynamic link modules in a server data processing system;

   means for coupling a data processing system to said server data processing system via a data processing system network;

   means for executing said hardware setup program within said server data processing system, in response to a request to execute said hardware setup program by said data processing system;

   [allowing a client data processing system to access a server data processing system via a data processing system network;

   receiving a request over the data processing system network for an execution of a hardware setup program by the server data processing system;

   executing the hardware setup program on the server data processing system;

   sending to the client data processing system one or more dynamic link modules for the hardware setup operation; and]

   means for modifying [the] hardware configuration data [on the client] within said data processing system according to instructions generated [by the] from said execution of said hardware setup program [on the] within said server data processing system; and

   means for de-coupling said data processing system from said server data processing system after a completion of said hardware setup operation.

6.   (Amended) The [hardware setup method] apparatus of Claim 5, wherein[: if the] when said hardware setup operation required by [the client] said data processing system exists [on] within an operating system running on [the client] said data processing system, [the] said hardware setup program performs [the] said hardware setup operation by using a service provided by [the] said operating system.

7.   (Amended) The [hardware setup method] apparatus of Claim 5, wherein[:

the hardware setup operation is performed by changing one or more items of hardware configuration data on the client data processing system] when said hardware setup operation required by said data processing system does not exist within an operating system running on said data processing system, said hardware setup program calls a BIOS program within said data processing system to perform said hardware setup operation.

8.   (Amended) The [hardware setup method] apparatus of Claim 5, wherein said apparatus further includes means for transferring one or more of said dynamic link modules from said server data processing system to said data processing system via said data processing system network as a result of said execution of said hardware setup program [:
if the hardware setup operation required by the client data processing system does not exist on an operating system running on a client data processing system, the hardware setup program calls a BIOS program on the client data processing system, and uses the BIOS program to perform the hardware setup operation].

9.   cancelled
10.   cancelled
11.   cancelled
12.   cancelled
13.   cancelled
14.   cancelled
15.   cancelled
16.   cancelled

17.   (Amended) A [data processing system] computer program product for performing a hardware setup operation on a data processing system, said computer program product comprising:

program code means for storing a hardware setup program and a plurality of dynamic link modules in a server data processing system;

[instructions for accessing] program code mean for coupling a data processing system to said server data processing system[, by a client data processing system,] via a data processing system network;

[instructions for requesting over the data processing system network] program code means for executing said [an execution of a] hardware setup program [by the] within said server data processing system, in response to a request to execute said hardware setup program by said data processing system;

[instructions for receiving, in the client data processing system, one or more dynamic link modules for a hardware setup operation; and]

[instructions] <u>program code means for</u> modifying [the] hardware configuration data [on the client] <u>within said</u> data processing system according to instructions generated [by the] <u>from said execution of said</u> hardware setup program [on the] <u>within said</u> server data processing system<u>; and</u>

<u>program code mean for de-coupling said data processing system from said server data processing system after a completion of said hardware setup operation.</u>

18.   (Amended) The [data processing system] <u>computer</u> program product of Claim 17, wherein[:
the hardware setup operation is performed by changing one or more items of hardware configuration data on the client data processing system] <u>when said hardware setup operation required by said data processing system does not exist within an operating system running on said data processing system, said hardware setup program calls a BIOS program within said data processing system to perform said hardware setup operation.</u>

19.   (Amended) The [data processing system] <u>computer</u> program product of Claim 17, wherein[:
the hardware setup operation is performed by changing one or more items of hardware configuration data on the client data processing system] <u>when said hardware setup operation required by said data processing system does not exist within an operating system running on said data processing system, said hardware setup program calls a BIOS program within said data processing system to perform said hardware setup operation.</u>

20.   (Amended) The [data processing system] <u>computer</u> program product of Claim 17, wherein <u>said computer program product further includes program code means for transferring one or more of said dynamic link modules from said server data processing system to said data processing system via said data processing system network as a result of said execution of said hardware setup program.</u> [:
if the hardware setup operation required by the client data processing system does not exist on an operating system running on a client data processing system, the hardware setup program calls a BIOS program on the client data processing system, and uses the BIOS program to perform the hardware setup operation.]

21.   cancelled
22.   cancelled
23.   cancelled
24.   cancelled
25.   cancelled
26.   cancelled
27.   cancelled
28.   cancelled
29.   cancelled
30.   cancelled

31. cancelled
32. cancelled
33. cancelled
34. cancelled
35. cancelled
36. cancelled
37. cancelled
38. cancelled
39. cancelled
40. cancelled

HARDWARE SETUP METHOD

CROSS REFERENCE TO RELATED APPLICATION

5   This application claims priority from Japanese Patent

Application 11-055104, filed 03/03/99 (MM/DD/YY), which is

commonly assigned with the present application and is hereby

incorporated by reference. The contents of the present

application are not necessarily identical to the contents of

10   the priority document.

BACKGROUND OF THE INVENTION

1.   Technical Field:

15

The present invention generally relates to providing an

improved system of hardware setup in data processing systems

and in particular to the ability to reduce the resources and

effort required to accomplish such setup. Still more

20   particularly, the present invention relates to the setup of

hardware by means of a program operated over a data

processing system network.

2. Description of the Related Art:

The experience of repeatedly reconfiguring data processing system hardware absorbs the resources of organizations and the time of individuals for a seemingly limitless number of reasons. For instance, if a new peripheral device is added to a previously properly configured data processing system, it is often necessary to carry out a repetition of the hardware setup for pre-existing hardware so that the data processing system can recognize and drive the added device without conflict. The term "device" is a generic name for peripheral equipment (or peripheral devices) such as keyboards, mice, displays, and HDDs (Hard Disk Drives). Further, if the device drivers for an already installed device are upgraded, a hardware setup often needs to be performed to install the upgraded device driver into the data processing system. The device drivers are a program forming a part of the operating system (OS), which manages a device connected to the data processing system.

In the current state of the art, the hardware setup has

been carried out in the following three ways.

(1)   The data processing system has no hardware

setup program of its own, and leaves the hardware setup

5   entirely to the OS. In this case, for the Windows

(trademark) OS, the hardware setup is carried out

from the control panel.

(2)   The data processing system has its own

10   hardware setup program. In this case, the hardware

setup program is executed after the hardware is

installed into the data processing system.

(3)   The hardware setup program of (2) described

15   above also includes the function of (1) described

above. As an example of a hardware setup program of

this type, consider the ThinkPad Configuration Utility

provided for the IBM ThinkPad™, a notebook-sized

personal data processing system of International

20   Business Machines Corporation of the U.S. and IBM

Japan, Ltd. ThinkPad Configuration Utility is a

so-called integrated program, in which all of the

JA9-98-196

hardware setup items are collected into one place

without regard to whether they exist on the OS. By

simply executing this utility, any hardware setup

operation that is available on the data processing

5   system can be performed.

In case (1) above, the general-purpose nature of the OS

precludes it from carrying out setup operations that for

hardware that depends on the model of a data processing

10   system. Accordingly, it must be used in combination with a

hardware setup program of type (2). Case (3) above suffices

to perform the necessary hardware setup operations because

it integrates the functions of both the OS and the hardware

setup program that is native to the data processing system.

15

At any rate, the hardware setup operation is carried

out by executing the hardware setup program after installing

it into the data processing system. There are various ways

of installing the hardware setup program into the data

20   processing system. For instance, if the hardware setup

program is recorded on a portable recording medium such as a

diskette (or floppy disk (FD)) or CD-ROM, the portable

JA9-98-196

recording medium is set in a special drive and the hardware
setup program is installed. Further, if the hardware setup
program is stored on a server data processing system on a
network, the data processing system undergoing the hardware

5   setup operation is connected to the network, and the
installation is performed by downloading the hardware setup
program from the server data processing system.

The installation of the hardware setup program requires

10   substantial effort. The required effort becomes
increasingly significant in companies that have installed a
large number of data processing systems of the same model.
In the large number of data processing systems of the same
model owned by companies, hardware settings often need to be

15   uniform across all systems. In the current state of the
art, to perform the hardware setup, the hardware setup
program has to be installed for each individual data
processing system. Moreover, if the hardware setup program
is upgraded, it must be reinstalled on each system. If

20   there are many data processing systems to be set up, the
reinstallation requires a great effort.

JA9-98-196

The conventional hardware setup method is based on the premise that the hardware setup program must be installed into a data processing system. This creates a problem in that the installation requires a great effort if the
5   hardware setup operation is to be performed on many machines.

It would be desirable, therefore, to be able to perform the hardware setup operation without installing the hardware
10   setup program on the machine on which the hardware setup operation is to be performed. It would further be advantageous if the hardware setup operation could be performed from a server residing on a data processing system network.

15

SUMMARY OF THE INVENTION

It is the object of the present invention to provide a hardware setup method that enables a hardware setup

5   operation to be performed in a data processing system without installing a hardware setup program.

The hardware setup method related to the present invention is configured as follows. First, a server data

10   processing system connected to a network prepares a hardware setup program for performing a hardware setup operation, dynamic link modules for hardware setup operation to be used by the hardware setup program at the time of execution of the hardware setup program, and a small program for

15   executing the hardware setup program. Then, a data processing system undergoing the hardware setup operation accesses the server data processing system. The data processing system undergoing the hardware setup executes the small program on the server data processing system. The

20   executed small program transfers the dynamic link modules for the hardware setup operation to the data processing system undergoing the hardware setup. The small program

JA9-98-196

then executes the hardware setup program on the memory of the data processing system undergoing the hardware setup operation, while maintaining the program itself on the server data processing system.

5

As described above, in the hardware setup method related to the present invention, the hardware setup program is executed on the memory of the data processing system undergoing a hardware setup operation but maintained on the server data processing system on the network to which the data processing system undergoing the hardware setup operation is connected. Accordingly, the hardware setup program need not be installed into the data processing system undergoing the hardware setup. Thus, in the present invention, the hardware setup operation can be performed without installing the hardware setup program into the data processing system undergoing the hardware setup operation. This can solve the problem of the background art.

20

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The

5   invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

10

Figure 1 depicts the data processing systems and networks involved in the hardware setup method related to an embodiment of the present invention;

15   **Figure 2** illustrates the disposition of software components and data structures related to the hardware setup method of a further embodiment of the present invention (No. 1);

20   **Figure 3** further depicts the disposition of software components and data structures related to the hardware setup method of a further embodiment of the present invention (No.

2) at a later stage of the operation;

Figure 4 illustrates, through a flowchart, the operation of the hardware setup method related to a further embodiment of the present invention (No. 1);

Figure 5 is a flowchart showing the operation of the hardware setup method related to a further embodiment of the present invention (No. 2); and

Figure 6 depicts an example of the server data processing system used in the preferred embodiments of the present invention.

JA9-98-196

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures, and in particular
with reference to **Figure 1**, the preferred embodiment will

5   function in the environment of a computer network as
portrayed in **Figure 1**, a diagram showing the hardware setup
method related to an embodiment of the present invention.
Connected to a network **11** are a server data processing
system **12,** and a data processing system **14** undergoing the

10   hardware setup operation, hereafter the "client". The
server data processing system **12** includes an external
storage device **13** such as a hard disk drive. In the
external storage device **13,** a hardware setup program **15,**
dynamic link modules **16** for hardware setup operations, and a

15   small program **17** are stored.

The hardware setup program **15** is a program for setting
up the hardware of the client data processing system **14.**
The dynamic link modules **16** for hardware setup include

20   functions and subroutines that are invoked and used by the
hardware setup program **15,** and program modules such as

JA9-98-196

device drivers. The small program **17** is a program executed by the data processing system **14** to perform the hardware setup. The hardware setup method related to the embodiment will be described below with reference to **Figure 1**.

5

First, the data processing system **14** to perform the hardware setup accesses the server data processing system **12** through the network **11**. Then, it executes, on the server data processing system **12**, the small program **17** stored in the server data processing system **12**. The client data processing system **17** accepts the dynamic link modules for hardware setup from the server data processing system **12**. Then the small program **17** executes the hardware setup program **15** on the server data processing system **12**. The executed hardware setup program **15** uses the transferred dynamic link modules **16** for hardware setup to perform the hardware setup operation on the client data processing system **14**. This completes the hardware setup of the data processing system **14**.

20

In accordance with this embodiment, the execution of

JA9-98-196

the hardware setup program **15** is carried out on the server

data processing system **12,** and thus, after the execution,

the hardware setup program does not remain on the client

data processing system **14.** This can solve the various

5   problems with the prior art.

In the above described embodiment, an example using the

dynamic link modules **16** for hardware setup has been shown.

The contents of the dynamic link modules **16** for hardware

10   setup depend on the instructions of the hardware setup

program **15.** The hardware setup program **15** is made up mainly

of programs in an execution form, which have an extension

"EXE." The hardware setup program **15** includes libraries

having an extension "DLL," and device drivers having

15   extensions "VXD" and "SYS." The hardware setup program **15**

calls these libraries and device drivers at the time of

execution of the hardware setup program. The libraries

contain functions or subroutines called and used by the

program in executing the hardware setup program. The device

20   drivers are a programs, which provide communication between

the data processing system and peripheral devices. The

allow the data processing system to drive the hardware of

the peripheral device.

However, the above libraries also include those that
are not related to the hardware setup (for instance, the one
5   related to screen display). These libraries that are not
related to the hardware setup are not included in the
dynamic link modules **16** for hardware setup. Further, the
hardware setup program **15** may be constructed to use only
device drivers as the dynamic link modules **16.**

10

A further embodiment related to the present invention
will be described below, covering the case in which the
hardware setup program has both libraries and device drivers
as the dynamic link modules for hardware setup. **Figures 2**
15   **and 3** explain the hardware setup method related to this
embodiment. Connected to a network **21** are a server data
processing system **22** and a client data processing system **23.**
The term "client data processing system **23**" is used herein.
However, the client data processing system **23** in **Figures 2**
20   **and 3** is not necessarily an element of a client server
system. The client data processing system **23** is
substantially the same as the "data processing system **14** to

JA9-98-196

perform hardware setup" shown in **Figure 1**.

The client data processing system **23** includes a user

area **24**, OS (operating system) **25**, BIOS **29**, and hardware **30**.

5   The network **21** can take various forms, for instance, LAN

(Local Area Network), WAN (Wide Area Network), and Internet.

The server data processing system **22** can take various forms,

for instance, the server machine in a client server system

(C/S system), and a Web site in the Internet (also known as

10   WWW (World Wide Web) server).

The client data processing system **23** can take various

forms, for instance, a client machine in a client server

system (C/S system), and various data processing systems

15   connected to the Internet. The user area **24** is an area in

which application programs and data are developed. The

application program is a generic name of data processing

system programs used by the user for a certain application.

It is also simply called an "application." In this

20   embodiment, only the execution method of a hardware setup

program **31** is discussed. For a length of time after the

beginning, no change is seen in the status of the client

JA9-98-196

data processing system **23,** so the user area **24** is not shown
in **Figure 2.**

The OS (operating system) **25** is basic software that
5   manages programs, data, and hardware to efficiently process
the task given to the client data processing system **23.**
Although **Figure 2** shows only registries **26,** library groups
27, and device driver groups **28** as the structural elements
of the OS **25,** the OS **25** includes various programs in
10   addition to those.

The registries **26** are files in which the setup
information of device drivers and applications is recorded.
If a hardware setting is changed, the hardware setup data in
15   the registries **26** is also changed. The library groups **27**
are a collection of functions and subroutines invoked and
used by programs.

The device driver groups **28** are a collection of
20   programs forming a part of the OS **25,** which manages each
peripheral equipment device, (or hardware **30)** connected to
the client data processing system **23.** The BIOS (Basic

JA9-98-196

Input/Output System) **29** is positioned between the OS **25** and

the hardware **30,** and it starts up the system and provides

the functions such as Plug and Play (PnP) and power

management. The BIOS was originally a program for

5   controlling the input/output performed by the OS between

pieces of the hardware (namely, a basic input/output system

as represented by its name). However, the BIOS was

developed for single-task OSs, and as the multitasking OS

such as Windows 95™, Windows 98™, and OS/2™ has entered

10   widespread use, emphasis has been put on the functions such

as PnP and power management, replacing the original role of

the basic input/output system. The device driver groups **28**

control the input/output between the OS 25 and the hardware

30.

15

Now, with reference to **Figures 2 and 3,** the hardware

setup method related to this embodiment will be described.

The hardware setup program **31,** library files **32,** device

driver files **33,** and small program **34** are provided in the

20   server data processing system **22.** Specifically, they are

stored in the hard disk drive included in the server data

processing system **22.** The hardware setup program **31** is a

JA9-98-196

program for setting up the hardware of the client data

processing system **23**. The library files **32** are files in

which a plurality of libraries are stored. The libraries

are a function or subroutine invoked and used by the

5   hardware setup program **31** at the time of execution of the

hardware setup program.

The device driver files **33** are files in which device

drivers are stored. Device drivers are programs forming a

10   part of the OS, which manages a device connected to

the client data processing system **23**. The small programs **34**

are programs that the client data processing system **23**

executes on the server data processing system **22**. The

hardware setup method related to this embodiment will be

15   described below with reference to the flowchart shown in

Figure 4.

First, the client data processing system **23** connects to

the network **21** to access the server data processing system

20   **22** (**step S41**). Then, the client data processing system **23**

executes the small program **34** on the server data processing

system **22** (**step S42**). The small programs **34** transfers

libraries **32a** and device drivers **33a** necessary for the

hardware setup of the client data processing system **23** to

the client data processing system **23** from the library files

32 and the device driver files **33** of the server data

5   processing system **22** (**step S43**). The state of the client

data processing system **23** in this condition is shown in

Figure 3. The client data processing system **23** stores the

transferred libraries **32a** and device drivers **33a** in the user

area **24**. The small programs **34** executes the hardware setup

10 program **31** on the memory of the client data processing

system **23**, while storing the program itself on the server

data processing system **22** (**step S44**).

Now, the operation of the hardware setup program **31** is

15 described with reference to the flowchart shown in **Figure 5**.

First, the user of the client data processing system **23**

selects a hardware setting item required to be set up. That

is, a hardware setting item is selected for the hardware

setup program **31** (**step S51**). Then, the hardware setup

20 program **31** determines whether or not the selected hardware

setting item exists on the OS **25** (**step S52**). If the answer

is yes, the process goes to step **S53**, otherwise to step **S54.**

In step **S53**, the hardware setup program **31** uses a

service provided by the OS **25** to change the hardware

5   configuration data. In this case, the hardware setup

program **31** terminates the execution at this point, and

transfers control to the OS **25** of the client data processing

system **23.**

10   In **step S54**, the hardware setup program **31** calls the

BIOS **29**. And, it changes the hardware configuration data on

the menu of the BIOS **(step S55)**. In this case, the

hardware setup program **31** terminates the execution at this

point, and transfers control to the OS **25** of the client data

15   processing system **23**. The OS **25** having received control

from step **S53** has the changed hardware configuration data,

because the hardware configuration data was changed by the

service itself. The OS **25** uses the changed hardware

configuration data to modify the contents of the registries

20   **26.**

The OS **25** having received control from **step S55** gets

the changed hardware configuration data from the BIOS **29**.

The OS **25** uses the changed hardware configuration data to

modify the contents of the registries **26**. Now, an example

5   of the server data processing system used in this embodiment

is described with reference to **Figure 6.** The server data

processing system **60** is constructed as follows. To a

high-speed CPU - memory bus **61,** a CPU (Central Processing

Unit) **62,** and a main memory **64** are connected. To the CPU -

10   memory bus **61,** an I/O (Input/Output) bus **65** of a relatively

slow speed is connected via a bus adapter **63.** Respectively

connected to the I/O bus **65** are a hard disk drive (HDD) **67**

via a hard disk controller (HDC) **66,** a floppy disk drive

(FDD) **69** via a floppy disk controller (FDC) **68,** and a

15   network **71** via an I/O controller **70.** In **Figure 6,** only the

main parts are shown. The server data processing system is

made up of many parts other than those parts listed.

As the CPU **62,** microprocessors from Intel Corporation

20   of the U.S., International Business Machines Corporation of

the U.S., Sun Microsystems Inc. of the U.S., and the like

can be used. The main memory **64** is constructed using a DRAM

(Dynamic Random Access Memory). The type and memory

capacity of the DRAM depend on the use of the server data

processing system **60.**

5

Since the CPU - memory bus **61** for connecting the CPU **62**

and the main memory **64** depends on the architecture of the

CPU **62,** the one originally designed by the maker of the

server data processing system **60** is used. As the I/O bus

10   **65,** for instance, a PCI bus can be used. PCI (Peripheral

Component Interconnect) bus is a bus standard prescribed by

the PCI Special Interest Group: a group for standardization

in which several hundreds of companies including IBM of the

U.S. and Compaq Computer Corporation of the U.S. are taking

15   part, with Intel Corporation being the core of it).

As the hard disk drive (HDD) **67,** one having a large

capacity is used so that it can take responsibility as the

server data processing system. In addition to a stand-alone

20   disk drive, a disk array (for example, RAID: Redundant Array

of Inexpensive Disks), in which a plurality of disk devices

is arranged in an array, can be used.

The network **71** may be any of various ones such as LAN

(Local Area Network), WAN (Wide Area Network), and Internet,

depending on the use status of the server data processing

system. The hardware setup program **31,** library files **32,**

5   device driver files **33,** and small program **34,** shown in

Figure 2, are mounted on the hard disk drive (HDD) **67.**

The preferred embodiments of the hardware setup program

related to the present invention have been described above.

10   The implementation of the hardware setup method related to

the present invention requires only the connection of the

data processing system to be set up for hardware to the

network. The network is not limited to a special one. It

may be any of various ones, for instance, LAN (Local Area

15   Network), WAN (Wide Area Network), and Internet.

In accordance with the embodiments, the following

advantages can be obtained. Since the hardware setup

program is executed on the server data processing system,

20   the hardware setup can be provided without installing the

hardware setup program into the data processing system that

is being configured.

The hardware setup of a plurality of data processing systems can be carried out without installing the hardware setup program itself on the machines undergoing the setup operation. This gives great benefit to companies which have installed a large number of data processing systems of the same model. In the data processing systems owned by such companies, the same hardware setting needs to be imposed as a repeated standard. Conventionally, to perform the hardware setup, the hardware setup program has been installed for each individual data processing system. However, if the hardware setup program is upgraded, it must be reinstalled. If there are many data processing systems to be set up, the reinstallation requires much effort. In the embodiments, such effort can be reduced.

The server data processing system can prepare hardware setup programs corresponding to various models of machines or operating systems. Accordingly, the data processing system to be set up for hardware can realize the hardware setup without becoming conscious of the model or the operating system used. The server data processing system can always prepare the newest hardware setup program. In the

embodiments, even if the hardware setup program is executed once, the hardware setup program itself does not remain in the data processing system on the user side. Accordingly, the data processing system on the user side can always use

5   the newest hardware setup program. With this, the user need not check the version of the hardware setup program. This results in reduction in the number of times the user makes inquiries to the help center.

10   Since it is not necessary to preload (preinstall) the hardware setup program in the data processing system, it is not necessary to prepare a temporary version of hardware setup program when announcing the release of a new product. As a result, a longer period of time can be taken for

15   developing a hardware setup program, so a hardware setup program which is inexpensive, though of high-quality, can be provided.

The above described hardware setup methods according to

20   the embodiments of the present invention can be made into a program (hereinafter referred to as "hardware setup execution program") using various programming languages. The

JA9-98-196

hardware setup execution program is recorded on a
machine-readable recording medium. As the recording medium,
portable recording media such as ROM (Read Only Memory),
EEPROM (Electrically Erasable Programmable Read Only

5   Memory), and flash EEPROM for a memory device, floppy disk
(FD), CD-ROM (read only memory using compact disc), and MO
(Magneto-Optic) disc which are mounted on a data processing
system system, or the external storage device provided in a
server data processing system connected to a network can be

10   used.

The hardware setup execution program recorded on a
recording medium is taken into the server data processing
system **60** as follows. If the recording medium having

15   recorded thereon the hardware setup execution program
related to the embodiment is a floppy disk (FD), the FD is
loaded into the FDD **69,** and the hardware setup execution
program recorded on the FD is read in. And, the hardware
setup execution program is written to the hard disk (HDD)

20   **67.** This also applies to the case in which the recording
medium having recorded thereon the hardware setup execution
program is another portable recording medium such as a

JA9-98-196

CD-ROM or MO disc. If the recording medium is an external
storage device on a network, the hardware setup execution
program related to the embodiment, recorded on the external
storage device, is downloaded through a network **71**. And,
the downloaded hardware setup execution program is stored in
the hard disk (HDD) **67**.

It is important to note that while the present
invention has been described in the context of a fully
functional data processing system and/or network, those
skilled in the art will appreciate that the mechanism of the
present invention is capable of being distributed in the
form of a computer usable medium of instructions in a
variety of forms, and that the present invention applies
equally regardless of the particular type of signal bearing
medium used to actually carry out the distribution.
Examples of computer usable mediums include: nonvolatile,
hard-coded type mediums such as read only memories (ROMs) or
erasable, electrically programmable read only memories
(EEPROMs), recordable type mediums such as floppy disks,
hard disk drives and CD-ROMs, and transmission type mediums
such as digital and analog communication links.

While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.

JA9-98-196

CLAIMS:

What is claimed is:

1   1. A hardware setup method comprising:

2   accessing a server data processing system, by a

3   client data processing system, via a data processing

4   system network;

5   requesting over the data processing system network

6   an execution of a hardware setup program by the server

7   data processing system;

8   receiving, in the client data processing system,

9   one or more dynamic link modules for a hardware setup

10   operation; and

11   modifying the hardware configuration data on the

12   client data processing system according to instructions

13   generated by the hardware setup program on the server

14   data processing system.

1   2. The hardware setup method of Claim 1, wherein:

2   if the hardware setup operation required by the

3   client data processing system exists on an operating

4   system running on the client data processing system,

5   the hardware setup program performs the hardware setup

6   operation by using a service provided by the operating

7   system.

1   3. The hardware setup method of Claim 1, wherein:

2   the hardware setup operation is performed by

3   changing one or more items of hardware configuration

4   data on the client data processing system.

1   4. The hardware setup method of Claim 1, wherein:

2   if the hardware setup operation required by the

3   client data processing system does not exist on an

4   operating system running on a client data processing

5   system, the hardware setup program calls a BIOS program

6   on the client data processing system, and uses the BIOS

7   program to perform the hardware setup operation.

1   5. A hardware setup method comprising:

2   allowing a client data processing system to access

3   a server data processing system via a data processing

4   system network;

5   receiving a request over the data processing

6   system network for an execution of a hardware setup

7   program by the server data processing system;

8   executing the hardware setup program on the server

9   data processing system;

10   sending to the client data processing system one

11   ◦ or more dynamic link modules for the hardware setup

12   operation; and

13   modifying the hardware configuration data on the

14   client data processing system according to instructions

15   generated by the hardware setup program on the server

16   data processing system.

1   6. The hardware setup method of Claim 5, wherein:

2   if the hardware setup operation required by the

3   client data processing system exists on an operating

4   system running on a client data processing system, the

5   hardware setup program performs the hardware setup

6   operation by using a service provided by the operating

7   system.

1   7. The hardware setup method of Claim 5, wherein:

2   the hardware setup operation is performed by

3   changing one or more items of hardware configuration

4   data on the client data processing system.

1   8. The hardware setup method of Claim 5, wherein:

2   if the hardware setup operation required by the

3   client data processing system does not exist on an

4   operating system running on a client data processing

5   system, the hardware setup program calls a BIOS program

6   on the client data processing system, and uses the BIOS

7   program to perform the hardware setup operation.

1   9. A hardware setup method comprising:

2   accessing a server data processing system, by a

3   client data processing system, via a data processing

4   system network;

5   requesting over the data processing system network

6   an execution of a hardware setup program by the server

7   data processing system;

8   receiving, in the client data processing system,

9   one or more library files containing libraries used in

10   executing the hardware setup program and/or one or more

11   device driver files containing device drivers used in

12 executing the hardware setup program; and

13 modifying the hardware configuration data on the

14 client data processing system according to instructions

15 generated by the hardware setup program on the server

16 data processing system.

1 10. The hardware setup method of Claim 9, wherein:

2 if the hardware setup operation required by the

3 client data processing system exists on an operating

4 system running on a client data processing system, the

5 hardware setup program performs the hardware setup

6 operation by using a service provided by the operating

7 system.

1 11. The hardware setup method of Claim 9, wherein:

2 the hardware setup operation is performed by

3 changing one or more items of hardware configuration

4 data on the client data processing system.

1 12. The hardware setup method of Claim 9, wherein:

2 if the hardware setup operation required by the

3 client data processing system does not exist on an

4   operating system running on a client data processing

5   system, the hardware setup program calls a BIOS program

6   on the client data processing system, and uses the BIOS

7   program to perform the hardware setup operation.

1   13. A hardware setup method comprising:

2   allowing a client data processing system to access

3   a server data processing system via a data processing

4   system network;

5   receiving a request over the data processing

6   system network for an execution of a hardware setup

7   program by the server data processing system;

8   executing the hardware setup program on the server

9   data processing system;

10   sending to the client data processing system one

11   or more library files containing libraries used in

12   executing the hardware setup program, one or more

13   device driver files containing device drivers used in

14   executing the hardware setup program; and

15   modifying the hardware configuration data on the

16   client data processing system according to instructions

17   generated by the hardware setup program on the server

JA9-98-196

18   data processing system.

1   14. The hardware setup method of Claim 13, wherein:

2   if the hardware setup operation required by the

3   client data processing system exists on an operating

4   system running on a client data processing system, the

5   hardware setup program performs the hardware setup

6   operation by using a service provided by the operating

7   system.

1   15. The hardware setup method of Claim 13, wherein:

2   the hardware setup operation is performed by

3   changing one or more items of hardware configuration

4   data on the client data processing system.

1   16. The hardware setup method of Claim 13, wherein:

2   if the hardware setup operation required by the

3   client data processing system does not exist on an

4   operating system running on a client data processing

5   system, the hardware setup program calls a BIOS program

6   on the client data processing system, and uses the BIOS

7   program to perform the hardware setup operation.

1   17.   A data processing system program product for hardware

2   setup, comprising:

3   instructions for accessing a server data

4   processing system, by a client data processing system,

5   via a data processing system network;

6   instructions for requesting over the data

7   processing system network an execution of a hardware

8   setup program by the server data processing system;

9   instructions for receiving, in the client data

10   processing system, one or more dynamic link modules for

11   a hardware setup operation; and

12   instructions for modifying the hardware

13   configuration data on the client data processing system

14   according to instructions generated by the hardware

15   setup program on the server data processing system.

1   18.   The data processing system program product of Claim 17,

2   wherein:

3   if the hardware setup operation required by the

4   client data processing system exists on an operating

5   system running on the client data processing system,

JA9-98-196

6   the hardware setup program performs the hardware setup

7   operation by using a service provided by the operating

8   system.

1   19. The data processing system program product of Claim 17,

2   wherein:

3   the hardware setup operation is performed by

4   changing one or more items of hardware configuration

5   data on the client data processing system.

1   20. The data processing system program product of Claim 17,

2   wherein:

3   if the hardware setup operation required by the

4   client data processing system does not exist on an

5   operating system running on a client data processing

6   system, the hardware setup program calls a BIOS program

7   on the client data processing system, and uses the BIOS

8   program to perform the hardware setup operation.

1   21. A data processing system program product for hardware

2   setup, comprising:

3   instructions for allowing a client data processing

4   system to access a server data processing system via a

5   data processing system network;

6   instructions for receiving a request over the data

7   processing system network for an execution of a

8   hardware setup program by the server data processing

9   system;

10   instructions for executing the hardware setup

11   program on the server data processing system;

12   instructions for sending to the client data

13   processing system one or more dynamic link modules for

14   the hardware setup operation; and

15   instructions for modifying the hardware

16   configuration data on the client data processing system

17   according to instructions generated by the hardware

18   setup program on the server data processing system.

1   22. The data processing system program product of Claim 21,

2   wherein:

3   if the hardware setup operation required by the

4   client data processing system exists on an operating

5   system running on a client data processing system, the

6   hardware setup program performs the hardware setup

7   operation by using a service provided by the operating

8   system.

1   23. The data processing system program product of Claim 21,

2   wherein:

3   the hardware setup operation is performed by

4   changing one or more items of hardware configuration

5   data on the client data processing system.

1   24. The data processing system program product of Claim 21,

2   wherein:

3   if the hardware setup operation required by the

4   client data processing system does not exist on an

5   operating system running on a client data processing

6   system, the hardware setup program calls a BIOS program

7   on the client data processing system, and uses the BIOS

8   program to perform the hardware setup operation.

1   25. A hardware setup system comprising:

2   means for accessing a server data processing

3   system, by a client data processing system, via a data

4   processing system network;

JA9-98-196

5   means for requesting over the data processing

6   system network an execution of a hardware setup program

7   by the server data processing system;

8   means for receiving, in the client data processing

9   system, one or more dynamic link modules for a hardware

10   setup operation; and

11   means for modifying the hardware configuration

12   data on the client data processing system according to

13   instructions generated by the hardware setup program on

14   the server data processing system.

1   26. The hardware setup system of Claim 25, wherein:

2   if the hardware setup operation required by the

3   client data processing system exists on an operating

4   system running on the client data processing system,

5   the hardware setup program performs the hardware setup

6   operation by using a service provided by the operating

7   system.

1   27. The hardware setup system of Claim 25, wherein:

2   the hardware setup operation is performed by

3   changing one or more items of hardware configuration

JA9-98-196

4   data on the client data processing system.

1   28. The hardware setup system of Claim 25, wherein:

2   if the hardware setup operation required by the

3   client data processing system does not exist on an

4   operating system running on a client data processing

5   system, the hardware setup program calls a BIOS program

6   on the client data processing system, and uses the BIOS

7   program to perform the hardware setup operation.

1   29. A hardware setup system comprising:

2   means for accessing a server data processing

3   system, by a client data processing system, via a data

4   processing system network;

5   means for receiving a request over the data

6   processing system network for an execution of a

7   hardware setup program by the server data processing

8   system;

9   means for fulfilling the request over the data

10   processing system network for the execution of the

11   hardware setup program by the server data processing

12   system;

JA9-98-196

13   means for sending to the client data processing

14   system one or more dynamic link modules for the

15   hardware setup operation; and

16   means for modifying the hardware configuration

17   data on the client data processing system according to

18   instructions generated by the hardware setup program on

19   the server data processing system.

1   30. The hardware setup system of Claim 29, wherein:

2   if the hardware setup operation required by the

3   client data processing system exists on an operating

4   system running on a client data processing system, the

5   hardware setup program performs the hardware setup

6   operation by using a service provided by the operating

7   system.

1   31. The hardware setup system of Claim 29, wherein:

2   the hardware setup operation is performed by

3   changing one or more items of hardware configuration

4   data on the client data processing system.

1   32. The hardware setup system of Claim 29, wherein:

2   if the hardware setup operation required by the

3   client data processing system does not exist on an

4   operating system running on a client data processing

5   system, the hardware setup program calls a BIOS program

6   on the client data processing system, and uses the BIOS

7   program to perform the hardware setup operation.

1   33. A data processing system, comprising:

2   a CPU, a main memory, an external storage device,

3   and a network connection device, wherein the external

4   storage device is a recording medium containing a data

5   processing system program product; the data processing

6   system program product having instructions for:

7   accessing a server data processing system, by a

8   client data processing system, via a data processing

9   system network;

10   requesting over the data processing system network

11   an execution of a hardware setup program by the server

12   data processing system;

13   receiving, in the client data processing system,

14   one or more dynamic link modules for a hardware setup

15   operation; and

16   modifying the hardware configuration data on the

17   client data processing system according to instructions

18   generated by the hardware setup program on the server

19   data processing system.

1   34.   The data processing system of Claim 33, further

2   comprising a reader for reading in the recorded contents of

3   the recording medium.

1   35.   The data processing system according to Claim 33,

2   wherein said reader is a portable recording medium reader.

1   36.   The data processing system according to Claim 33,

2   wherein said reader is a network connection device.

1   37.   A data processing system, comprising:

2   a CPU, a main memory, an external storage device,

3   and a network connection device, wherein the external

4   storage device is a recording medium containing a data

5   processing system program product; the data processing

6   system program product having instructions for:

7   allowing a client data processing system to access

JA9-98-196

8   a server data processing system via a data processing

9   system network;

10   receiving a request over the data processing

11   system network for an execution of a hardware setup

12   program by the server data processing system;

13   executing the hardware setup program on the server

14   data processing system;

15   sending to the client data processing system one

16   or more dynamic link modules for the hardware setup

17   operation; and

18   modifying the hardware configuration data on the

19   client data processing system according to instructions

20   generated by the hardware setup program on the server

21   data processing system.

1   38.   The data processing system of Claim 37, further

2   comprising a reader for reading in the recorded contents of

3   the recording medium.

1   39.   The data processing system according to Claim 37,

2   wherein said reader is a portable recording medium reader.

JA9-98-196

1   40.   The data processing system according to Claim 37,

2   wherein said reader is a network connection device.